



PILATUS **300K**

**Unrivalled data quality for
time resolved experiments**



PILATUS 300K

The PILATUS 300K detector system combines the high frame rate of a PILATUS 100K with the large area of 85 mm x 106 mm². It is perfectly suited for all applications where you require a medium sized area detector combined with a high frame rate.



It is based on the newly developed CMOS hybrid-pixel technology and operates in single-photon-counting mode. It excels with its compact size, high frame rate and the outstanding capabilities which are common to all DECTRIS detector systems.

The PILATUS 300K detector system is air-cooled and therefore very simple in its operation and handling. It is ready to use and comes as a complete system with detector, PC with Linux OS and the data acquisition and analysis software TVX.

Applications

- Material science (MS)
- X-ray diffraction (XRD)
- Surface diffraction (SD)
- Small-angle scattering (SAXS)
- Time-resolved experiments
- Non-destructive testing

Key features

- Direct detection of X-rays in single-photon-counting mode
- Radiation-tolerant design
- High dynamic range
- Short readout time
- High frame rates
- High counting rates
- No dark current or readout noise
- Adjustable threshold to suppress fluorescence
- Excellent point-spread function
- Electronically gateable
- Shutterless operation

Technical specifications

Number of modules	1 × 3
Sensor	Reverse-biased silicon diode array
Sensor thickness	320 μm
Pixel size	172 × 172 μm ²
Format	487 × 619 = 301,453 pixels
Area	83.8 × 106.5 mm ²
Intermodule gap	y: 17 pixels, 5.5% of total area
Dynamic range	20 bits (1:1,048,576)
Counting rate per pixel	> 2 × 10 ⁶ X-ray/s
Energy range	3–30 keV
Quantum efficiency (calculated)	3 keV: 80 % 8 keV: 99 % 15 keV: 55 %
Energy resolution	500 eV
Adjustable threshold range	2–20 keV
Threshold dispersion	50 eV
Readout time	2.3 ms
Framing rate	200 Hz
Point-spread function	1 pixel
Data formats	Raw data, TIF, EDF, CBF
External trigger/gate	5V, 3 different modes
Software interface	Through socket connection; clients for EPICS, SPEC and stand-alone operation are available
Cooling	Air-cooled
Power consumption	48 W
Dimensions (WHD)	160 × 194 × 289 mm
Weight	Approx. 7.5 kg

DECTRIS Ltd.
Neuenhoferstrasse 107
5400 Baden
Switzerland
+41 56 500 2100 phone
+41 56 500 2101 fax
sales@dectris.com
www.dectris.com

